

DANGAN[®] TYPE III

6 Bars, 3 Bars type

High speed auto filler for liquids and pastes

[Basic Specifications]

Line speed	4 ~ 25 m/min (13.1 ~ 82 ft/min)
Seal pitch	6 Bars: 30 ~ 70mm (1.2 ~ 2.75 in.) 3 Bars: 70 ~ 180mm (2.75 ~ 7 in.)
Film width	50 ~ 200mm (2 ~ 7.8 in.)
Max. packing capacity	6 Bars: 500packs/min 3 Bars: 400packs/min
Power supply	AC200V +/- 20V, 5.3KVA, 3 Phase 50/60 Hz
Air supply	0.5MPa or higher, 80NL/min
Machine size	1545mm(L)x1000mm(W)x2315mm(H) 5.07 ft(L)x3.3 ft(W)x7.6 ft(H)
Machine weight	Approx. 1000kg (2,200 lbs.)

(Conditions varies depending on the sealing width etc.)



Taisei Lamick Co., Ltd.

873-1 SHIMO-OHSAKI, SHIRAOKA CITY,
SAITAMA, 349-0293 JAPAN

URL : <http://www.taiselamick.com>

TEL : +81-480-97-0320

FAX : +81-480-97-0323

E-MAIL : overseas@lamick.co.jp